

**Stoner**

# Stoner® E236

## Urethane Mold Release

### Product Description

**Stoner® E236 Urethane Mold Release** is specially formulated as a release agent and anti-stick lubricant for molded urethanes and similar materials. Provides fast, easy part removal from molds and multiple part releases per application. Improves molding efficiency in many processes including injection, pour cast, and extrusion molding. Economical – a light coating produces best results.

### E236 Urethane Mold Release ADVANTAGES:

- Saves time—lets you remove urethane parts from molds quickly and easily.
- Improves part appearance and reduces defects caused by sticking.
- Contains no Class I (CFC) or Class II (HCFC) Ozone Depleting Substances.
- Contains no chlorinated solvents such as 1,1,1 trichloroethane or methylene chloride.
- Colorless and non-staining.

### Uses

**Stoner® E236 Urethane Mold Release** is a release agent and anti-stick lubricant for molded urethanes and similar materials.

### Direction for Use

#### **Recommended Procedure**

Shake well. Hold can 10 to 12 inches from mold surface. Apply a thin mist coating on mold surface for best results.

### Storage and Handling

Do not puncture or incinerate container. Do not expose container to heat or store at temperatures above 120 °F. Keep container away from and do not use near sparks, open flame, heated surfaces, or other ignition sources.

### Packaging

**Stoner® E236 Urethane Mold Release** is available in:

- Case of 12, 12 oz cans
- OR
- Individual 12 oz cans

### Technical Assistance

Call: 800-227-5538 or 1 (717) 786-7355

Visit: [StonerMolding.com](http://StonerMolding.com)

